

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |    |  |  |
|--|----|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |    | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |    | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | XX | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |    |  |  |

March 26, 1951

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Skelly Oil Company

L. Van Etten

Well No. 9

in the

Company or Operator

Lease

SE/4 NW/4 SW/4

of Sec. 9

T

20S

R

37E

N. M. P. M.

Monument

Field

Lea

County.

The dates of this work were as follows:

March 22, 1951

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on March 21, 1951

and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled to total depth of 3770'. Ran & cemented 7" OD casing at 3531'. Cemented in two stages using Halliburton process with 200 sacks around casing shoe and 1000 sacks through Halliburton DV tool set at 2753'. Cement circulated to surface on second stage. Let cement set 48 hrs. and on March 22, 1951, drilled plug and tested casing shut-off. Shut-off tested OK.

Witnessed by E. R. Deitz Skelly Oil Company Foreman  
Name Company Title

Subscribed and sworn before me this

26th day of March, 1951

*E. R. Deitz*

Notary Public

MY COMMISSION EXPIRES AUG. 19, 1952

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name E. R. Deitz

Position Dist. Supt.

Representing Skelly Oil Company  
Company or Operator

Address Drawer "D", Hobbs, New Mexico

Remarks:

APPROVED  
MAR 27 1951  
Date

*W. J. [Signature]*  
Oil & Gas Inspector  
Title