## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**

SECTE 9 1861

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modification advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as appropriately the collection of the Commission. See additional instructions in the Rules and Returns of

Indicate natur	re of notice by checking	below:	
OTICE OF INTENTION TO TEST CASING	NOTICE OF	INTENTION TO SHOOT OR	
SHUT-OFF	XX CHEMIC	CALLY TREAT WELL	
TOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF OTHER	INTENTION TO PULL OR WISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF	INTENTION TO PLUG WELL	
OTICE OF INTENTION TO DEEPEN WELL			
Hot	obs, New Mendico	March 21, 1951	
	Place		
IL CONSERVATION COMMISSION, anta Fe, New Mexico entlemen:			
Skelly Oil Company	Van Etten	Well No 9 in SE/4 NW/	4 S
Company or Operator Lea. 9 208 , R. 37E	.8e	Visual sea. Management	
Lea County		Eurit (;6-Ronusent Field.	
Drilled to total depth of 3 3531'. Comented in two standards sacks around casing shoe an	3770°. Ran & com ages using Hallib ad 1000 sacks thr	ented 7" ()D casing at ourton process with 200 ough Halli, burton DV tool	
Drilled to total depth of 3 3531'. Cemented in two sta	RULES AND REGULATED ROOM REPORT REPORT RESERVED TO THE RESERVE	ented 7" ()D casing at surton process with 200 ough Halliburton DV tool on second stage. Will 1 at approximately 11:30	
Drilled to total depth of 3 3531'. Cemented in two states around casing shoe and set at 2753'. Cement circulat cement set 48 hrs. and P.M. will drill plug and te	RULES AND REGULATED BY 1000. Ran & commission Hallib and 1000 sacks thrulated to surface on March 22, 1950 est casing shut-out.	ented 7" ()D casing at surton process with 200 ough Halliburton DV tool on second stage. Will at approximately 11:30 ff.	
Drilled to total depth of 3 3531'. Cemented in two states around casing shoe and set at 2753'. Cement circulat cement set 48 hrs. and P.H. will drill plug and temporary and the set at 2753'.	RULES AND REGULATED BY 1000. Ran & commission Hallib and 1000 sacks thrulated to surface on March 22, 1950 est casing shut-out.	ented 7" ()D casing at purton process with 200 ough Halliburton DV tool on second stage. Will at approximately 11:30 ff.	
Drilled to total depth of 3 3531'. Cemented in two states around casing shoe and set at 2753'. Cement circulat cement set 48 hrs. and P.H. will drill plug and temporary and the set at 2753's and P.H. will drill plug and temporary and the set 48 hrs.	RULES AND REGULATED BY 1000. Ran & commission Hallib and 1000 sacks thrulated to surface on March 22, 1950 est casing shut-out.	ented 7" ()D casing at surton process with 200 ough Halliburton DV tool on second stage. Will at approximately 11:30 ff.	
Drilled to total depth of 3 3531'. Cemented in two states around casing shoe and set at 2753'. Cement circulet cement set 48 hrs. and P.H. will drill plug and temporary and the set at 2753'.	RULES AND REGULATED BY 1000. Ran & commission Hallib and 1000 sacks thrulated to surface on March 22, 1950 est casing shut-out.	sented 7" ()D casing at purton process with 200 ough Halliburton DV tool on second stage. Will l at approximately 11:30 ff.  Skelly Oil Company  Company or Operator  Dist. Supt.	
Drilled to total depth of 3 3531. Cemented in two states around casing shoe and set at 2753. Cement circulat cement set 48 hrs. and P.M. will drill plug and te	RULES AND REGULATED BY	Skelly Oil Company  Company or Operator  Dist. Supt.  Send communications regarding well to	

Hobbs, New Mexico