

Santa Fe, New Mexico

RECEIVED

NOTICE OF INTENTION TO DRILL

FEB 23 1951

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice with such changes will be returned to the sender. Submit this notice in triplicate. One copy must be retained following approval. See additional instructions in Rules and Regulations of the Commission.

HOBBS OFFICE

Hobbs, New Mexico

February 22, 1951

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as
Skelly Oil Company

L. Van Etten

Well No. 9

in NW/4 SW/4

Company or Operator

Lease

of Sec. 9, T. 20S, R. 37E, N. M., P. M., Monument Field, Lea County.

N

The well is 1650 feet (N.) (S) of the South line and 990 feet (E.) (W.) of the West line of Section 9-20S-37E

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is Lucell Van Etten

Address Monument, New Mexico

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary tools from surface to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
14-1/2"	10-3/4"	40#	New	200'	Cemented	200
8-3/4"	7"	36#	New	3450'	Cemented	200
				1120'	2-Stage Tool	200

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3600 feet.

Additional information:

Two stages will be used in cementing the 7" casing. Two-stage tool will be at approximately 1120' and sufficient cement used to circulate to surface.

Approved _____, 19____

except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name

Skelly Oil Company

Address

Drawer "D", Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

Oil & Gas