

Santa Fe, New Mexico

RECEIVED

MAY 15 1951

OIL CONSERVATION COMMISSION

HOBBS OFFICE

DUPLICATE

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

May 11, 1951

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Place

Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Skelly Oil Company

L. Van Etten

Well No. 10

in C NE/4 SW/4 SE/4

Company or Operator

Lease

of Sec. 9, T 20S, R 37E

N. M., P. M.,

Monument

Field, Lea

County.

N

The well is 990 feet (N.) (S.) of the south line and 1650 feet (E.) (W.) of the east line of Section 9-20S-37E

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is L. Van Etten


Address Monument, New Mexico

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary tools from surface to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

| Size of Hole | Size of Casing | Weight Per Foot | New or Second Hand | Depth | Landed or Cemented | Sacks Cement |
|--------------|----------------|-----------------|--------------------|-------|--------------------|--------------|
| 14-1/2"      | 10-3/4"        | 40#             | New                | 200'  | Cemented           | 200          |
| 8-3/4"       | 7"             | 36#             | New                | 3600' | Cemented           | 200          |
|              |                |                 |                    | 2750' | 2-Stage tool       | 1000         |

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3800' feet.

Additional information: Two stages will be used in cementing the 7" casing. Two-stage tool will be at approximately 2750' and sufficient cement used to circulate to surface.

Approved MAY 16 1951, 19\_\_\_\_  
except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name Skelly Oil Company

Address Drawer "D", Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

Roy Yankovsky  
Oil & Gas Inspector

1951