

NEW MEXICO STATE LAND OFFICE
OFFICE OF THE STATE GEOLOGIST
 SANTA FE, NEW MEXICO

MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas Inspector if possible.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF SHOOTING WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF		REPORT ON REPAIRING WELL	XX
REPORT ON RESULT OF ABANDONMENT OF WELL			

Hobbs, New Mexico January 22, 1934

PLACE

DATE

Mr. E. H. Wells State Geologist,

Santa Fe, N. Mex.

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Company State Well No. 33 in the

NW¹ of Sec. 4, T. 19 S, R. 33 E, N. M. P. M.,

Hobbs Oil Field, Lea County.

The dates of this work were as follows: January 14, 1934

Notice of intention to do the work was (was not) submitted on Form SG 105 on October 25, 1933, and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

A Guiberson Spiral Tubing Packer to run on 3" A.P.I. 10thd. External Upset Tubing was run inside 6 5/8" OD 26# casing to shut off water coming from upper Hobbs pay horizon. The bottom of the packer was set at 4089'6", and all indications are that a successful water shut-off has been made. The well was swabbed for five days but due to the excessive amount of water which it was necessary to pump into the hole before the packer was run to kill the well, the swabbing was unsuccessful. Rods were then run in the well and it is now pumping and flowing an average of sixty four barrels of pipe line oil daily, pumping slowly. The production will, no doubt, increase as the water in the hole is dissipated.

DUPLICATE

Subscribed and sworn to before me this

22nd day of January, 1934.

[Signature]

NOTARY PUBLIC.

My commission expires October 17, 1934

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name J. P. Libbey

Position Production Foreman

Representing Stanolind Oil & Gas Company

Address Hobbs, New Mexico

COMPANY OR OPERATOR.

FEB 27 1934

RECEIVED AS O. K.

[Signature]

