

NEW MEXICO STATE LAND OFF.
OFFICE OF THE STATE GEOLOGIST
 SANTA FE, NEW MEXICO

MISCELLANEOUS REPORTS ON WELLS

Submit this report in duplicate to the State Geologist or proper Oil and Gas Inspector within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of water shut-off, result of abandonment of well, and other important operations, even though the work was witnessed by the State Geologist or Oil and Gas Inspector. Reports on minor operations need not be signed and sworn to before a notary public, but such operations should be witnessed by an Oil and Gas Inspector if possible.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF SHOOTING WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF		REPORT ON REPAIRING WELL	XX
REPORT ON RESULT OF ABANDONMENT OF WELL			

Hobbs, New Mexico

March 19, 1934

PLACE

DATE

Mr. E. H. Wells State Geologist,
 Santa Fe, N. Mex.

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Company State Well No. 33 in the
 NW 1/4 of Sec. 4, T. 19 S, R. 33 E, N. M. P. M.,
Hobbs Oil Field, Lea County.

The dates of this work were as follows: February 15th to March 9th, inclusive

Notice of intention to do the work was (~~was not~~) submitted on Form SG 105 on
October 25, 1934, and approval of the proposed plan was (~~was not~~) obtained. (Cross
 out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Due to an unsuccessful shut-off being obtained after two packers were run on February 2nd, these packers and the tubing was pulled. A whip stack was then cemented from 4034' to 4020'. The 4" whip stack anchor is set and cemented from 4028', the top of the lost cable tools, to 4034'. After the cement was allowed to set the old hole was drilled out to 4034', the bottom of the whip stack, where the bit started out in new hole. The well was then drilled to a total depth of 4215', on March 5th. A 5 1/2" OD X 11'8" Quiberson Spiral Tubing packer was run and set at 4110'. All indications are that a successful water shut-off has been made. The well was swabbed for twenty nine hours before the well started flowing. The well is now flowing an average of one hundred and twenty six barrels of net oil with one barrel of water, flowing through a 1" choke. The production and net oil has increased since the well was swabbed in.

DUPLICATE

Subscribed and sworn to before me this

19th day of March, 1934.

[Signature]

NOTARY PUBLIC.

I hereby swear or affirm that the information given above is true and correct.

Name J. J. Tillin

Position Production Foreman

Representing Stanolind Oil & Gas Company

Address Hobbs, New Mexico

COMPANY OR OPERATOR.

My commission expires October 17th, 1934

Remarks:

APPROVED AS O. K.

[Signature]

