

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

State ☐	Fee ☒
--------------------------------	---

SUNDY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☐

OTHER- Water Injection

1. Unit Agreement Name

8. Farm or Lease Name

South Hobbs (GSA) Unit

9. Well No.

33

10. Field and Pool, or Wildcat

Hobbs GSA

Name of Operator

AMOCO PRODUCTION COMPANY

Address of Operator

P.O. BOX 68 HOBBS, NEW MEXICO 88240

Location of Well

UNIT LETTER G 2310 FEET FROM THE North LINE AND 1650 FEET FROM
THE East LINE, SECTION 4 TOWNSHIP 19-S RANGE 38-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3623.1 RDB

12. County

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

REFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
WELL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

OTHER Cmt Squeeze and Acidize ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MISU 5-13-85, rel pkr, and POH w/ tbg and pkr. Ran 2-3/8" tbg and tagged PBTD at 4254'. Pulled tbg to 3950' and plugged well back w/ 18 SXS SN. Top of SN = 4066'. Capped w/ 5' calseal to 4061'. POH. RIH w/ 4 1/2" cmt ret and SA 3942' and established inj rate. Spotted 250 gal 15% HCL acid. Pumped 50 sx class "C" neat cmt and 50 sx class "C" w/ add. Squeezed to 500 psi. Rev out 32 sx, and POH. RIH w/ 3-7/8" bit and tagged cmt let at 3942'. DO 3942'-3982'. Circ clean. DO 3982'-4061' and press tested squeeze to 1000 psi. - OK. DO calseal and SN 4061'-4183'. Circ clean and POH. Ran 2-3/8" notched collar and 2-3/8" tbg. CO SN 4183'-4254'.

OTS-NMOC-D-H, 1-JRB, 1-FSN, 1-NLG

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Theresa L. Galar

TITLE Administrative Analyst

DATE 27 May 1985

ORIGINAL SIGNED BY EXTON
DISTRICT 1 SUPERVISOR

APPROVED BY

TITLE

DATE

MAY 29 1985

CONDITIONS OF APPROVAL, IF ANY:

Circ clean. and POH. RIH w/ 4 1/2 pkr and SA 4106'. Pumped 3000 gal 15% NE HCL acid w/ add. Flushed w/ 35 BW. Rel pkr and POH. RIH w/ 4 1/2" pkr and 2-3/8" tbg. Pkr SA 3948'. Loaded backside w/ 42 bbl pkr fluid and tested to 500 psi - OK. MOSW 5-20-85. Commenced inj 5-20-85 Finaled W.O. 5-22-85 w/ inj after W.O. = 980 BPD on vac.