## NEW MEXICO STATE LAND OFFICE SANTA FE, NEW MEXICO

## **DEPARTMENT OF THE STATE GEOLOGIST**

## NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible.

If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

| State Geologist, Santa Fe, New Mexico.  Dear Sir:  You are hereby notified that we intend to test the shut-off of water in  Well No. 3 in Sw. of Sec. 4 , T. 198  N. M. P. M., Bobb Oil Field Lea  on Aug. 10. 19 30 . 26 lb. casing was landed cemented formation at a depth of feet on Aug. 5.  200 sacks of Oil Well Special cement were used. The method used in placing the cement was as follows: Helliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:  Additional information: | , R. 38E County,      |
|--|-----------------------|
| Santa Fe, New Mexico.  Dear Sir:  You are hereby notified that we intend to test the shut-off of water in  Well No. 3 in Sw. of Sec. 4 , T. 198  N. M. P. M., Hobbs Oil Field Lead  on Aug. 10, 19 30 . 26 lb. casing was landed cemented formation at a depth of 3988 feet on Aug. 5.  200 sacks of 011 Well Special cement were used The method used in placing the cement was as follows: Halliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:                                     | , R. 38E County,      |
| You are hereby notified that we intend to test the shut-off of water in  Well No. 3 in Swo of Sec. 4 , T. 198  N. M. P. M., Bobbs Oil Field Les  on Aug. 10, 19 30 . 26 lb. casing was landed cemented formation at a depth of 3988 feet on Aug. 5.  200 sacks of Oil Well Special cement were used The method used in placing the cement was as follows: Helliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:  | , R. 38E County,      |
| Well No. 3 in Sw. of Sec. 4 , T. 195  N. M. P. M., Bobbs Oil Field Lea  on Aug. 10, 19 30 . 26 lb. casing was landed cemented formation at a depth of 3968 feet on Aug. 5,  200 sacks of Oil Well Special cement were used. The method used in placing the cement was as follows: Halliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:  | , R. 38E County,      |
| N. M. P. M.,  on Aug. 10, 19 30 . 26 lb. casing was landed cemented formation at a depth of 3988 feet on Aug. 5.  200 sacks of 011 Well Special cement were used.  The method used in placing the cement was as follows: Helliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:   | in Line               |
| on Aug. 10, 1930. 26 lb. casing was cemented formation at a depth of 3988 feet on Aug. 5.  200 sacks of Oil Well Special cement were used. The method used in placing the cement was as follows: Helliburton  Fluid level will be bailed to a depth of Dry feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:   | in <b>Line</b>        |
| formation at a depth of  | . in <b>Line</b>      |
| formation at a depth of  |                       |
| The method used in placing the cement was as follows: Halliburton  Fluid level will be bailed to a depth of  | 19_ <b>50</b>         |
| Fluid level will be bailed to a depth of feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:   | l.                    |
| Fluid level will be bailed to a depth of feet and left und 12 hours before your inspection.  Adjacent property owners have been notified as follows:   |                       |
|  | isturbed for at least |
| Additional information:  |                       |
|  |                       |
|  |                       |
| Approved Sincerely yours.  |                       |
| Except as follows: The Widwest Ref:  | ining Company         |
| By the South   | Company or Operator.  |
| Position Field Supt.   | <u> </u>              |
|  | ~ well to             |
| Send communication regardin  Name The lidest Ref.  |                       |
| State Geologist or Oil and Gas Inspector.  |                       |