DISTRIBUTION	NEW MEXICO OIL CONSERVATION COMMISSION		Form C+103 Supersedes Old C-102 and C+103 Ellective 1-1-65
FILE	MEA WEXICO OIL COIL	JERTATION COMMISSION	Sa. Indicate Type of Leaso
U.5.G.S.			State X Fee
LAND OFFICE			5. State Oil & Gas Leave No.
OPERATOR	}		A-1212
(DO NOT USE THIS FOR FOR PAGE CAT	RY HOTICES AND REPORTS ON THE SECOND	PACE 13 & Olly Edgal Medical	7. Unit Agreement Name
I. OIL X WELL OTHER-			South Hobbs (GSA) Unit
Amoco Production Company			South Hobbs (GSA) Unit
P.O. Drawer A, Levelland, Texas 79336			9. Well No. 16
4. Lecution of Well			10. Field and Fool, or Wildest
WHIT LETTER D 660 FEET FROM THE NORTH LINE AND 660 FEET FROM			Hobbs - GSA
THE WEST LINE, SECTION	ON 4 TOWNSHIP 19-	S RANGE 38-E NMPM.	
minimini in	15. Elevetion (Show whether	DF, RT, GR, etc.)	12. County
	3626' RDB	<u> </u>	Lea
	Appropriate Box To Indicate 1 ATENTION TO:	Nature of Notice, Report or Oth	ner Data REPORT OF:
		. 57	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	PLUG AND ABANDONMENT
TEMPCHARILY ABANDON		CASING TEST AND CEMENT JOG	PEDG AND ABARDONNICAT
PULL OR ALTER CASING	CHANGE PLANS	OTHER	
OTHER			
		tails, and give pertinent dates, including	estimated date of starting any proposes
work) SEE RULE 1103.			
tubing. Bridge plug s log ran 3875'-2790'. Swabbed down to 4090 4083-4053. Tested tul 30 min. Test OK. Sque 50 sx 1/4# med. grine 44 hrs. drilled cemen 4064'. Tested casing Lost circulation. Pu 4097'. Acidized Zone Treated all zones. Pa	set at 3876'. Tested casi Perforated 4053-4064, 40'. Acidized 4053'-4200' whing to 2500# for 30 min. eezed perforations 4053-4d tuff plug. Reversed out and retainer 3976-3997 to 600# for 30 min. Test lled tubing, drill collar III w/3500 gal 15% NE HOulled tubing and packer. urned well to production.	rods and pump. Ran retreing to 500# for 30 min. Test 177-4083, 4102-4200 with 2 1/500 gal 15% NE. Swabbed Test OK. Tested casing at 1064 and 4077-4083 w/100 states and 57 ft. cement. It is 10K. Tagged bridge plug at 10K. Tagged bridge pl	st OK. Cement bond jet shots per foot. zone II 4005-4096 and nnulus to 500# for x Class C cement and ubing. Waited on cement Ran out of cement at t 4096' and drilled. treating packer to alls in 4 stages Installed API 320
CEMENT BOND LOG ATTAI OC 4-12-78 COMP 5-8-78			
18. I hereby certify that the information	about is true and complete to the best	of my knowledge and belief.	
Sand J	Yorter MILE ASS	t. Administrative Analyst	DATE 5-30-78
() ig. Sign	ned by	· ·	
way Sex	ton		9.478 · · · · · · · · · · · · · · · · · · ·
APPROVED BY	•		
0+4 NMOCC-H 1-Div	1-Susp 1-DLP		