


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



DUPLICATE MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	X
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 14, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Stanolind Oil & Gas Company State "A" Tract 3 Well No. 26 in the

Company or Operator SW/4 of Sec. 4, T. 19-S, R. 38-E, N. M. P. M.,
Hobbs Field, Lea County.

The dates of this work were as follows: completed July 2nd, 1947

Notice of intention to do the work was was not submitted on Form C-102 on June 13 19 47

and approval of the proposed plan was was not obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

SEE REVERSE SIDE

Witnessed by John D. Culp Stanolind Oil & Gas Co. Field Engineer
Name Company Title

Subscribed and sworn before me this 14th

I hereby swear or affirm that the information given above is true and correct.

day of July, 19

Name Lea Smith

Position Field Supt.

Lea County, N. Mexico Notary Public

Representing Stanolind Oil & Gas Co.
Company or Operator

My commission expires 2-23-1950

Address Box F; Hobbs, N.M.

Remarks:

APPROVED
JUL 16 1947

Ray Yarbrough
Name
Oil & Gas Inspector
Title

T.D. 4190'. 8-5/8" Casing set at 3977'. Tested 8-5/8" Casing with 1200 psi. Located leak at 1043'. Perforated 3101' to 3099' with 4 shots per foot. Circulated cement through perforations to surface using 425 sacks. Tested casing with 850 psi, held o.k. Drilled out to TD 4190, set 5 1/2" liner 3939' to 4190' with 83 sacks cement. Tested line o.k. Perforated liner 4132' to 4136', 4140' to 4144', 4146' to 4166', 4170 to 4178' with 4 shots per foot. Swabbed down to 1500' off bottom, acidized with 500 gallons, swabbed down to 1800', reacidized with 2000 gallons. Well started flowing approximately 205 barrels fluid per day 50% oil in 24 hours.