

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
Amoco Production Company
3. Address of Operator
P. O. Box 68, Hobbs, NM 88240
4. Location of Well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 4 TOWNSHIP 19-S RANGE 38-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3610' DF
12. County
Lea

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
FULL OR ALTER CASING ☐ OTHER ☐
SUBSEQUENT REPORT OF:
REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in service unit 6-26-81. Ran 7-5/8" bit, 10 4-5/8" drill collars, and 2-7/8" tbg. Tagged cmt. retainer at 497'. Drilled out to 1507'. Set pkr. at 1018'. Reset pkr. to 317'. Cmt. w/200 SX Class C w/additives w/max. squeeze 500 PSI. Pulled tbg. & pkr. Ran bit, drill collars and tbg. Tagged cmt. at 470'. Drilled to 645'. Pulled tbg. Ran pkr. & tbg. w/pkr. set at 700'. Raised pkr. to 300'. Cmt. w/250 SX Class C w/additives w/max. squeeze 2500 PSI. Pulled tbg. & pkr. Ran bit, drill collars, & tbg. Tagged cmt. at 296' & drilled to 640' w/stringer to 676'. Lowered bit to 1507' & tagged cmt. Drilled out cmt. 1507'-1720'. Tagged cmt. 2255'. Drilled to 2369'. Tagged cmt. 3519' & drilled out 3588'-3780'. Lowered bit to 3900' & tagged cast iron bridge plug. Displaced hole w/clean water. Drilled cast iron bridge plug. Pulled tbg. & bit. Ran tbg. & pkr. w/pkr. set at 3737'. Reset pkr. to 2334'. Pulled tbg. & pkr. Ran bridge plug & set at 3499'. Spotted 15' sn on bridge plug & tbg. Ran pkr. & tbg. to 1971'. Pumped 150 SX Class C and 250 SX Class C neat. Drilled out 2260'-2375 w/stringers 2431'. Set pkr. at 2028'. Raised pkr. to 1380'. Cmt. w/245 SX Class C w/additives. Pulled tbg. & pkr. Ran bit, drill collars, & tbg. Tagged cmt. at 1490 & drilled out to 1690'. Pulled tbg. & tools. Preparing to run pkr. & tbg.

0+4-NMOCD, H 1-Hou 1-Susp 1-CLF

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cathy L. Sorman TITLE Assist. Admin. Analyst DATE 9-25-81

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: