## STATE OF NEW MEXICO ENERGY AND MIMERALS DEPARTMENT

DISTRIBUTION	1	
BANTA PE		1
FILE		!
U.S.O.S.		
LAND OFFICE .		1
OPPGATOR	7	,

## OIL CONSERVATION DIVISION

DISTRIBUTION		P. O. BO	X 2088		Form C-103 • Revised 10-1-7		
FILE	SANTA	FE, NEV	MEXICO 875	0.1			
U.S.O.S.					Se. Indicate 7		
LAND OFFICE				•	State X	Fne	
OPPRATOR	)				5, biole Ch. 6	Gas Lease No.	
SUNDR	Y NOTICES AND RE	PORTS ON	I WELLS		THITT		TT:
SUNDRY NOTICES AND REPORTS ON WELLS  100 NOT USE THIS FORM FOR MEROPALS TO CRITICAL FOR PLUS BACK TO A DIFFERENT RESERVOIR.  100 NOT USE THIS FORM CATION TO PROPERTY OF PROPERTY OF PROPERTY OF PROPERTY.		IFSERVOIR.					
1. OIL CAS WILL	отния. Inje	ction We	11		7, Unit Agree		
AMOCO PRODUCTION COMP	ANY				6. Furm or Lease Name		
3. Address of Operator					South Hobbs (GSA)		
P. O. Box 68, Hobbs,	NM 88240					32	
4. Location of Wall			100		10. field and Pool, or Wildcat		
UNIT LETTER F	1980 FEET FROM THE	Nort	h_ LINE AND	O FEET FROM	Hobbs GSA		m
THE West LINE, SECTION	ON 4 TOWNS	19	-S RANGE 3	8-E NMPM.			
	15. Elevation (	Show whether	DF, RT, GR, etc.)		12. County	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	11/4
	7////	3614'	KB		Lea		777;
Check	Appropriate Box To	Indicate 1	Nature of Notice	, Report or Oth	ier Data		
NOTICE OF IN	TENTION TO:			SUBSEQUENT	REPORT	OF:	
PERFORM REMEDIAL WORK	PLUG AND	ABANDON	REMEDIAL WORK		<b>A</b> 1	TERING CASING	_
TEMPORARILY ABANDON	, 200 and		COMMENCE DRILLING	: CONS.		UG AND ABANDONME	NT -
PULL OR ALTER CASING	CHANGE PL	ANS	CASING TEST AND CI	EMENT JOB			
			OTHER CONV	ert to injec	tion		<u> </u>
OTHER	<del></del>	LJ		-			
17. Duscribe Proposed or Completed Opwork) SEE RULE 1103.	erctions (Clearly state all	pertinent de	tails, and give pertine	nt dates, including	estimated date	of starting any pr	oposed
Moved in service unit out preventer. Pulle Tagged fill at 4198' out of hole. Ran 5" and 2-3/8" plastic co 100 bbls packer fluid tubing and packer. Rat 3990'. Seating ni Pressure tested packe injection 2-3-84. Su	d 2-7/8" tubing and cleaned out Lok-set plastic ated tubing. Ref. Packer would e-ran packer and pple landed at 3 r to 500 psi. To bject well curre	out of h from 419 coated p moved bl not set. tubing. 955'. F ested OK	ole. Ran 2-7 8 to 4244'. acker, 2-3/8" owout prevent Removed tre Pumped 100 inished loadi Moved off	/8" notched Circulated of plastic coater and instale bbls packer ng casing wiservice unit	collar and lean and ted seatilled tree led BOP. fluid and th packer	d tubing. pulled tubi ng nipple . Circulat POH with packer set	ing ted t
					<del>, , , , , , , , , , , , , , , , , , , </del>		<del></del>
0+5-NMOCD, H 1-R. E.		e to the best	of my knowledge and	belief.			wis
·ICHED Dary C. C	Wark	TITLE	Assist. Admin	. Analyst	DATE	2-24-84	66.7
Eddie V	V. Seay					FEB 28 1	384
Oil & Gas	Inspector	Y 1 7 1 F			DATE		