

NEW MEXICO STATE LAND OFFICE  
SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST  
NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Hobbs N. Mex., February 20th, 1933

Mr. E. H. Wells

State Geologist,  
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in State  
Well No. 29 in SE 1/4 of Sec. 4, T. 19, R. 38,  
N. M. P. M., Hobbs Oil Field Lea County,  
on February 23rd 1933 8 5/8" 36 lb. casing was ~~XXXXXX~~ cemented in line  
formation at a depth of 3978 feet on February 19th 1933  
150 sacks of El Toro special oil well cement were used.

The method used in placing the cement was as follows:

**Halliburton Method**

Fluid level will be bailed to a depth of \_\_\_\_\_ feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows: \_\_\_\_\_

Additional information:

**Shut off test will be made by maintaining 1200# pressure on casing for thirty minutes both before and after drilling cement plug.**

DUPLICATE 1620 RECD

Approved FEB 22 1933

Except as follows:

Sincerely yours,

**Stanolind Oil and Gas Company**

Company or Operator.

By

Position **Superintendent**

Send communication regarding well to

Name **C. G. Scott, Supt.**

Address **Stanolind Oil and Gas Company**

**Hobbs, New Mexico.**

State Geologist or Oil and Gas Inspector.