

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Odessa, Texas

March 22, 1950

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the Sun Oil Company
H.D. McKinley Well No. 1 in NE/4
Company or Operator Lease
of Sec. 5, T. 19-S, R. 38-E, N. M. P. M., Hobbs Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Move in rig, 250 bbl. test tank, mix tank gal mud, 40 Vls. #2, Krevistop/bbl. Load hole w/mud, pull tubg. check TD, clean out if needed. Run caliper log, gamma ray log, and dialog. If there are no holes in csg., then will rerun tubg. w/Guiberson spiral Gakum formation pk. seat-caliper log, test packer w/500#, if possible. Then wash in.

If there are holes in csg., then will run Baker scraper to TD, run Baker hydraulic under reamer & ream 191' of 6 1/4" open hole to 8" dia. run & cement 5 1/2" inner csg. string on bottom employing Baker multiplex cementing equip.. First stage 90 sac, 25 gal w/stage collar #3925' (250' off bottom) circulate excess cement out. Wait 8 hrs. - 2 nd. stage, cement to surface w/400 lbs. 45 gal, perf. csg. Fr-GR., wash perf. w/500 gals. acid (run temp. sur. if not circulated on out. above) - scrub wall in.

Approved MAR 22 1950, 19____
except as follows:

Sun Oil Company
Company or Operator
By C. S. Albright
Position Superintendent
Send communications regarding well to

OIL CONSERVATION COMMISSION,
By Roy Garbarough
Title _____

Name C. S. Albright
Address Box 2792, Odessa, Texas

