

NEW MEXICO OIL CONSERVATION COMMISSION DISTRICT OFFICE OCC
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

1957 OCT 10 AM 9:31

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

10-8-57
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation

H. D. McKinley NW/5
(Company or Operator) Well No. 1 in AC
NE 1/4 NE 1/4 of Sec. 5, T. 19, R. 38, NMPM, Hobbs Pool
(40-acre Subdivision) Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to eliminate communication between intermediate and oil string casing we propose the following: Under ream open hole 3920 - 4190, perforate 6-5/8" csg. at 3220 above Bowers pay with 4 jet shots. Set plug at 3250' and circulate water through casing perforations to surface. Retrieve plug, condition hole and run new 5" casing from surface to TD and cement both the 6-5/8" and 5" casing to surface. Drill plug to 4185, perforate 4100 - 4120, 4129 - 38, and 4145 - 57 with 4 shots per foot and acidize with approximately 1500 gallons acid. Test well and return to production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By: [Signature]
Title:

Pan American Petroleum Corporation
Company or Operator

By: R. L. Hendrickson

Position: Field Superintendent
Send Communications regarding well to:

Name: R. L. Hendrickson

Address: Box 68, Hobbs, New Mexico