

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
El. & Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-07627
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name McKinley
2. Name of Operator Amoco Production Company	8. Well No. 12
3. Address of Operator P. O. Box 3092, Houston, TX 77253	9. Pool name or Wildcat Bowe's Seven Rivers
4. Well Location Unit Letter <u>C</u> : <u>660</u> Feet From The <u>North</u> Line and <u>2310</u> Feet From The <u>West</u> Line Section <u>5</u> Township <u>19-S</u> Range <u>38-E</u> NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3630' DR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pull Prod Equipment
Perf 5½ csg at 455'; set retainer at 355'; squeeze perfs w/50st class "C" cmt; If cannot circulate cmt, squeeze 50 sx cmt
Drill out cmt retainer & cmt
Spot cmt plug from 2500' to 2600' and from 50' to surface
load wellbore w/10# saltgel mud between cmt plugs
Weld steel plate w/pressure valve & sign on top

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Matthew C. Wines TITLE Administrative Analyst DATE 9/14/90

TYPE OR PRINT NAME Matthew C. Wines TELEPHONE NO. 713/556-3744

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY JERRY SEKTON TITLE STATE ENGINEER DATE 9/14/1990

CONDITIONS OF APPROVAL, IF ANY:

FOR APPROVAL AND RECORD OF THE STATE ENGINEER'S OFFICE AND OPERATIONS FOR THE STATE OF NEW MEXICO