

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**Santa Fe, New Mexico**

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days of the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See original instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

**July 27, 1953**  
(Date)

**Hobbs, New Mexico**  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Stanolind Oil and Gas Company**  
(Company or Operator)

**State A Tract 4**  
(Lease)

**Hewgley Drilling Company**  
(Contractor)

Well No. **24** in the **SE**  $\frac{1}{4}$  **SW**  $\frac{1}{4}$  of Sec. **5**

**T19-S, R38-E**, NMPM, **Hobbs** Pool, **Lea** County.

**July 23 to July 25, 1953 Inclusive.**

The Dates of this work were as follows:

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan ~~(was)~~ (was not) obtained.

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

On July 23, 1953 ran 4298' of 5 $\frac{1}{2}$ " casing landed at 4307' with DV tool at 1505' and cemented 1st stage with 105 sacks of 4% gel plus 105 cubic feet of perlite followed with 100 sacks neat cement. Opened DV tool and circulated and cemented second stage with 100 sacks neat cement. After 30 hours WOC tested casing with 1050 psi for 30 min with no drop in pressure. Drilled staging collar and cement to top of float collar at 4239' and tested casing with 1000 psi for 30 minutes and as there was no drop in pressure completion operations were resumed.

Witnessed by **K. W. Huiatt**  
(Name)

**Stanolind Oil and Gas Company** **Production Foreman**  
(Company) (Title)

Approved:

**OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **Ralph H. Lendowski**

Position **Field Superintendent**

Representing **Stanolind Oil and Gas Company**

Address **Box 68, Hobbs, New Mexico**

**Ray Yankrough**  
(Name)  
**Oil & Gas Inspector**  
(Title)  
**JUL 28 1953**  
(Date)