

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

July 15, 1963

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Pan American Petroleum

Corporation

State "A" Tract 4

Well No. 8

in

L

(Company or Operator)

198

Lease

Hobbs

(Unit)

NW 1/4 SW 1/4 of Sec. 198, T. 19S, R. 38E, NMPM, Pool

(40-acre Subdivision)

Lea

County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 4310', FBD 4000', 5-1/2" CSA 4307'; perforations 4076'-80', latest test, June, 1963, 10 BW x 64 BW in 24 hours. In an effort to increase productivity we propose to squeeze perforations 4076'-80' with 100 sx cement below retainer set at 4060'. Sandril perforate intervals 3969'-72', 3990-93', 3998'-4001', 4005'-68', 4013'-16', 4025'-28', 4040'-43'. Wash with 500 gallons acid and free with 30,000 gal oil containing 1-2% sand per gallon. Swab in, evaluate and restore to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Pan American Petroleum Corporation

Original Signed by Company or Operator  
V. E. STALEY

By.....

Area Superintendent

Position.....

Send Communications regarding well to:

V. E. Staley

Name.....

Box 68 - Hobbs, New Mexico

Address.....