

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

S. E. Cone

Company or Operator

First Nat'l Bank Bldg. Lubbock, Texas

Address

Will Terry

Well No. 1

in NE SW SE

of Sec. 9

T. 19 S

Lease

R. 38, N. M. P. M. Hobbs Field, Lea County.

Well is 990 feet North of the North line and 1660 feet west of the East line of Sec. 9

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Will Terry Address Hobbs, N. M.

If Government land the permittee is Address

The Lessee is Address

Drilling commenced 4/8/48 19. Drilling was completed 5/4/48 19.

Name of drilling contractor Wise & Hawkins Address Hobbs, N. M.

Elevation above sea level at top of casing 3611 feet.

The information given is to be kept confidential until not confidential 19.

OIL SANDS OR ZONES

No. 1, from 4080 to 4125 No. 4, from to

No. 2, from 416 to 4172 No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	32	seamless	300						
5 1/2	15	"	4045						

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
9 3/4	8 5/8	300	150	halaburton pump		
7 3/4	5 1/2	4045	150	"	"	
	Temperature survey shows cement at 3280					

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		1000 15 % acid		5/1/48	4080 - 4125	
		3000 "		5/2/48	" "	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4172 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 5/4 May 4, 19. 48.

The production of the first 24 hours was 200 barrels of fluid of which 1 % was oil; %

emulsion; 99 % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 5th

day of May, 19. 48

S. E. Cone

Notary Public

My Commission Expires August 19, 1951

My Commission expires

Hobbs, N. M. Mexico May 5 1948

Name J. R. Cone

Position Agent

Representing S. E. Cone Company or Operator

Address Lubbock, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
Top anhy. 1620	to 1850	230	
1850	2620	770	Salt top 1850
2770			top Yates sand
2900			" Brown Line
4110			" Saltwater Shoal Bank San Adres
4162			top Hobbs pay