

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

OCT 18 1946

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report of results of testing liner.	

Hobbs, New Mexico

October 17, 1946

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company, Hobbs, New Mexico, Well No. 8 in the

N. 1/4 of Sec. 10, T. 10N., R. 10E., N. M. P. M., Hobbs Field, Lea County.

The dates of this work were as follows: October 11, 1946 and October 13, 1946.

Notice of intention to do the work was (was not) submitted on Form C-102 on October 4, 1946

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On October 11, 1946, a 5-1/2" liner was cemented from 4102' to 4201' w/100 sx. Previously, all junk had been fished out of hole. After 48 hours had elapsed, top of liner was tested by applying 600 psi, for 10 minutes. Pressure held. The eight feet of cement plug in liner was then drilled out and liner was again tested for shut off by swabbing hole dry. After 1 hour no fluid entered hole. Hole has been deepened below liner to 4205.

Witnessed by Ralph L. Gray Stanolind Oil and Gas Company Field Engineer

Name

Company

Title

Subscribed and sworn before me this 17th

I hereby swear or affirm that the information given above is true and correct.

day of October, 1946

Name R. L. GrayPosition Field EngineerRepresenting Stanolind Oil and Gas Company

Company or Operator

My commission expires 2-25-50

Address Box F, Hobbs, New Mexico

Remarks:

APPROVED

Date OCT 18 1946

Roy Yachura  
Name  
Oil & Gas Inspector  
Title