

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS OF WELLS

RECEIVED  
FEB 23 1946  
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico

February 20, 1946

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil & Gas Co.

Terry Tract 1

Well No. 26

in the

Company or Operator

Lease

SE/4 of SE/4

of Sec. 9

T. 19-S

R. 38-E

N. M. P. M.,

Hobbs

Field,

Lea

County.

The dates of this work were as follows: 3 January 1946 to 15 February 1946

Notice of intention to do the work was (and has) submitted on Form C-102 on December 18 19 45

and approval of the proposed plan was (has) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

T.D 4250. Plug back TD 4200. A cement plug was placed from 4027-4200, casing shot in numerous places and finally parted at 2410', 8-5/8" casing was then pulled and a 40-sack cement plug placed with the base at 2410'. The hole was then mudded with 11 tons of Easy-Mix clay. A 40-sack cement plug was then spotted at 1500' (base) in 10-3/4" casing. Twenty sacks cement was set as surface plug in casing and marker installed. Abandonment completed February 15, 1946.

Witnessed by G. V. Campbell  
Name

Stanolind Oil & Gas Co.  
Company

Prod. Foreman  
Title

Subscribed and sworn before me this 21st

I hereby swear or affirm that the information given above is true and correct.

day of February, 1946

Name Ralph H. Haveluck

Position Field Supt.

*R. G. Tucker*

R. G. Tucker Notary Public

Representing Stanolind Oil & Gas Co.  
Company or Operator

My commission expires 4-23-49

Address Box F, Hobbs, New Mexico

Remarks:

APPROVED

Date Feb 21 1946

*Roy Yarbrough*  
Oil & Gas Inspector

Title

