

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL OR RECOMPLETE

Notice must be given to the District Office of the Oil Conservation Commission and approval obtained before drilling or recompletion begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes must be submitted to the sender. Submit this notice in **QUINTUPPLICATE**. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

(Place)

July 27, 1953

(Date)

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Gentlemen:

You are hereby notified that it is our intention to commence the (Drilling) (Recompletion) of a well to be known as
Stanolind Oil and Gas Company

(Company or Operator)

State A Tract 6

(Lease)

Well No. **24**, in **F** The well is

(Unit)

located **1650** feet from the **North** line and **2310** feet from the **West** line of Section **9**, T**19-S**, R**38-E**, NMPM.

(GIVE LOCATION FROM SECTION LINE) **Hobbs** Pool, **Lea** County

D	C	B	A
E	x F	G	H
L	K	J	I
M	N	O	P

If State Land the Oil and Gas Lease is No. **S-2588**

If patented land the owner is

Address

We propose to drill well with drilling equipment as follows: **Rotary tools to total depth**

The status of plugging bond is **Blanket bond on file with Commission**

Drilling Contractor **Hewgley Drilling Company**
Midland, Texas

We intend to complete this well in the **San Andres** formation at an approximate depth of **4300** feet.

CASING PROGRAM

We propose to use the following strings of Casing and to cement them as indicated:

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
11"	8-5/8"	29.35#	Used	300'	140 SX
7-7/8"	5-1/2"	14#	New	4300'	*

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.)

* **Two Stage with D. V. tool set at approximately 1630' or top of salt section.**
1st stage: 105 sx cement 4% gel plus 105 cu. ft. perlite followed with 110 sx neat cement.

2nd stage: 100 sx neat cement

Approved....., 19.....
Except as follows:

28 1953

Sincerely yours,

Stanolind Oil and Gas Company

(Company or Operator)

By **Ralph L. Hendrickson**

Position **Field Superintendent**

Send Communications regarding well to

Name **R. L. Hendrickson**

Address **Box 68**

Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By **Noy Munkrough**

Title **Oil & Gas Inspector**