

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO <del>PERFORATE</del> Sandrill	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) Sand Oil Free	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

March 29, 1961  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation.

W. H. Terry Tract 1 Well No. 8 in J  
(Company or Operator) (Unit)  
NW 1/4 SE 1/4 of Sec. 9, T. 19-S, R. 30-E, NMPM, Hobbs Pool  
(40-acre Subdivision)  
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In an attempt to shut off water and increase productivity of well the following work is proposed:

Set drillable retainer at 4010 and squeeze perforations 4020-4030 with 100-200 mx. regular cement. Drill out to 4000'. Sandrill perforate 4021-24, 4028-31, 4041-44, 4051-54, 4057-60, 4065-68, 4074-77, 4082-85 using 12 minutes jetting time at each interval. Spot 500 gallons 15% acid across perforations followed with a sand free consisting of 30,000 gallons lease crude containing 2# sand per gallon. Overflush with 10 barrels of oil and restore to production.

Approved March 30 1961, 19\_\_\_\_  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By [Signature]  
Title \_\_\_\_\_

Pan American Petroleum Corporation  
Original Signed Company or Operator  
By V. E. STALEY

Position Area Superintendent  
Send Communications regarding well to:

Name V. E. Staley  
Address Box 68, Hobbs, New Mexico

