

NEW MEXICO STATE LAND OFFICE

SANTA FE, NEW MEXICO

DEPARTMENT OF THE STATE GEOLOGIST

NOTICE OF TEST OF WATER SHUT-OFF

Notice must be given to the State Geologist or to the proper Oil and Gas Inspector at least five days before the test. It is desirable that a representative of the Department of the State Geologist witness the water shut-off before drilling into the productive sand whenever possible. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to sender. Submit this notice in duplicate.

Hobbs N. Mex., March 21st, 1933

Mr. E. H. Wells

State Geologist,
Santa Fe, New Mexico.

Dear Sir:

You are hereby notified that we intend to test the shut-off of water in State
Well No. 29 in SW $\frac{1}{4}$ of Sec. 10, T. 19, R. 33,
N. M. P. M., Hobbs Oil Field Lea County,
on March 23rd 1933 10" 70 lb. casing was ~~drilled~~ cemented in red beds
formation at a depth of 128' 8" feet on March 20th 1933
75 sacks of Oil max oil well cement were used.

The method used in placing the cement was as follows:

Halliburton method

Fluid level will be bailed to a depth of dry feet and left undisturbed for at least 12 hours before your inspection.

Adjacent property owners have been notified as follows:

Additional information:

Re-cementing job on above casing - Casing originally cemented with 95 sacks on March 17th as shown on form SG-103 of that date - Water shut-off test made March 20th not successful (see form SG-106 Mar. 21st 1933)

Approved March 22 1933 Sincerely yours,

Except as follows:

After drilling cement plug at least 20 ft. of hole be made below bottom of casing and then bailed dry for 12 hour test

The Midwest Refining Company

Company or Operator.

By

Position District Superintendent

Send communication regarding well to

Name The Midwest Refining Company

Address Hobbs, New Mexico.

T. O. Stanley
State ~~Geologist~~ Oil and Gas Inspector.