$c: \mathbb{C}^{1}$

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Notice by Checking	r Below	
Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention to Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	Notice of Intention Repair (Other) casing leak	Notice of Intention (Other)	
OIL CONSERVATION COMMIS	SION Hobbs, New Mexico	September 1	0, 1954
Gentlemen:	(-1117)	(Sate)	
	tion to do certain work as described below at the	——————————————————————————————————————	
Stanolind Oil and Gas Company (Company or Operator)		Well No	
NE 1/4 SW 1/4 of Sec.			
(40-acre Subdivision)		•	
	County.		
/ T	FULL DETAILS OF PROPOSED PLAN		
(F	FULL DETAILS OF PROPOSED PLAN OLLOW INSTRUCTIONS IN THE RULES AN		
Supplementing procedure	OLLOW INSTRUCTIONS IN THE RULES ANd outlined in Form C-102, dated M	ED REGULATIONS)	leaks
Supplementing procedure	OLLOW INSTRUCTIONS IN THE RULES ANd outlined in Form C-102, dated M	ED REGULATIONS)	leaks
Supplementing procedure between 1182° and 1160° We propose to: Load hole and p Run new string Clean out and p	OLLOW INSTRUCTIONS IN THE RULES ANd outlined in Form C-102, dated M	ay 18, 1954, which located t to total depth and run l circulate cement to surfa	ogs.
Supplementing procedure between 1182' and 1160' We propose to: Load hole and p Run new string Clean out and p 500 gallons 159	e outlined in Form C-102, dated M ; pull tubing and packer. Clean out 5-1/2" casing to total depth and perforate to depth indicated by 1 6 regular acid and put well back	ay 18, 1954, which located t to total depth and run l circulate cement to surfa	ogs.
Supplementing procedure between 1182' and 1160' We propose to: Load hole and p Run new string Clean out and p	e outlined in Form C-102, dated M pull tubing and packer. Clean out 5-1/2" casing to total depth and perforate to depth indicated by 1 bregular acid and put well back Position	ay 18, 1954, which located to total depth and run licirculate cement to surfaces. Stimulate with approximation.	ogs. ce. ximately

Address.....Box..68 - Hobbs, New Mexico