

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, Hobbs, New Mexico, for approval. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE & Sand Frac	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)June 26, 1962
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation

State "A" Tract 9

Well No. 1 in C (Unit)

NE 1/4 of Sec. 15, T. 19S, R. 38E, NMPM., Hobbs Pool
(40-acre Subdivision) (Company or Operator)

TD 4364'

FULL DETAILS OF PROPOSED PLAN OF WORK Remedial Work
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

On production test 2-18-62, this well produced, on pump, 5 BO and 63 BW in 24 hours. In an effort to increase production and shut-off the water we propose set a retainer at 4130' and squeeze open hole section 4131-4364' with 100-200 sz cement. Cap the cast iron retainer with 10' cement. Perforate log indicated permeability from 4000' to 4110' with 2 shots per foot. Spot 1000 gallons LSTINE acid across perforations followed by sand-oil frac consisting of 30,000 gallons oil and 1/2 to 2# sand per gallon. Swab in and evaluate.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy Leslie A. Clements

Title.....

Pan American Petroleum Corporation

Company or Operator

Original Signed by:

By V. E. STALEYPosition Area Superintendent

Send Communications regarding well to:

Name V. E. StaleyAddress Box 68, Hobbs, New Mexico