
Santa Fe, New Mexico



SUPPLEMENTAL

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions by following it with (?). SUBMIT IN TRIPLICATE,

in the Rules and Regulations of the Commission. Indicate questionable data AREA 640 ACRES LOCATE WELL CORRECTLY Stanolind Oil and Gas Company Box "F", Hobbs, New Mexico Company or Operator Address State "A" Tract 9 38-E Ho bbs _Field, _ Well is 330 feet south of the North line and 330 feet west of the East line of NW/4 of Sec. 15 If State land the oil and gas lease is No. 2,056 Assignment No. If patented land the owner is If Government land the permittee is_ The Lessee is Stanolind Oil and Gas Company Address Box 591 Tulsa 2, Oklahom 1943 Drilling was completed September 29 September 14 Drilling commenced_ Name of drilling contractor Beekrien, Inc. Elevation above sea level at top of casing 3.588.4 The information given is to be kept confidential until___ OIL SANDS OR ZONES _ No. 4, from_ No. 7, from. No 6 from IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. _feet. _ No. 1, from No. 2, from. 4,268 No. 3, from____ No. 4, from Liner TASING RECORD KIND OF CUT & FILLED FROM PERFORATED PURPOSE WEIGHT PER FOOT AMOUNT MAKE SIZE FROM 52"OD 178 Baker *This liner was set at 4,151' with 60 sacks of cement in an effort to shut off the water bearing permeable section from 4,000 to 4,151'. MUDDING AND CEMENTING RECORD NO. SACKS OF CEMENT MIID GRAVITY METHOD USED WHERE SET AMOUNT OF MUD USED PLUGS AND ADAPTERS Heaving plug-Material___ _Length_ _____Depth Set___ Adapters-Material___ __Size_ RECORD OF SHOOTING OR CHEMICAL TREATMENT CHEMICAL USED QUANTITY DATE DEPTH CLEANED OUT SIZE SHELL USED Dowell XX 860 gal. 1-8-44 42301-531 Dowell XX 2700 gal. Dowell XX 2100 gal. Results of sheeting-or-chemical treatment Production was increased from 12 BOPD, no water to 70 BOPD and 70 BWPD. RECORD OF DRILL-STEM AND SPECIAL TESTS If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto. TOOLS USED _feet to______feet, and from______feet to_____feet Rotary tools were used from 4,143 Cable tools were used from feet to feet, and from feet to feet PRODUCTION Put to producing January 19 The production of the first 24 hours was 156 barrels of fluid of which 52 % was oil; 5 % If gas well, cu, ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas____ Rock pressure, lbs. per sq. in.____ **EMPLOYEES** T. H. Byrum J. W. Collins ______, Driller _____ W. H. Scarbrough _, Driller _ . Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 29th day of_____

Notary Public

Position Field Superintendent

Representing STANOLIND OIL AND CAS COMPANY

Company or Operator Address Box "F" Hobbs, New Mexico

My Commission expires 5-5-47

	<u> Santia, ya</u>		PRMATION RECORD
FROM	TO	THICKNESS	FORMATION
0 4.143 4.155 4.162 4.171 4.176 4.202 4.208 4.221 4.225 4.228 4.221 4.225 4.228 4.221 4.233 4.324 4.333 4.333 4.333 4.334 4.344 4.345 4.346 4.358 4.363	4,143 4,155 4,162 4,171 4,176 4,202 4,208 4,225 4,225 4,228 4,228 4,228 4,238 4,231 4,329 4,331 4,333 4,334 4,345 4,346 4,345 4,346 4,345 4,346	12 7 25 6 13 10 43 41 5 2 10	Original Total Depth Buff, granular lime White Buff "Top Sand Break 4,188' (-595') White Buff White Buff White Buff Gray Buff
PBTD	4,256 s		
1			
			And the state of t
	20		
			And the second of the second o
	eris de l'es v		
	1		