

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL	<input type="checkbox"/>	NOTICE OF INTENTION TO DRILL DEEPER	<input type="checkbox"/>
NOTICE OF INTENTION TO PLUG WELL	<input type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK	<input type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	<input type="checkbox"/>
NOTICE OF INTENTION TO SQUEEZE	<input type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	<input type="checkbox"/>
NOTICE OF INTENTION TO GUN PERFORATE	<input type="checkbox"/>	NOTICE OF INTENTION (OTHER)	<input type="checkbox"/>	NOTICE OF INTENTION (OTHER)	<input type="checkbox"/>

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

February 9, 1955

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amco Oil & **CORDCO DRILLING COMPANY** Terry Well No. **1** in **3** (Unit)
 C.P.M. **NM** 1/4 **EE** 1/4 of Sec. **22**, T. **19S**, R. **30E**, NMPM, **Hobbs** Pool
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The above described test has been drilled to total depth of 4200' into the San Andres formation. The hole has been cored from a depth of 3970' to total depth. Cores from the Grayburg section show a little porosity and staining in the last 30 feet but do not look promising. We propose, therefore, to cement 5 1/2" casing with 50 sacks, at a depth of 4140' and fracture the Grayburg between 4140' and a plugged back depth of 4194'. A Hydramite plug was set to plug the bottom six feet of hole and as a precautionary measure against water from the San Andres.

If the Grayburg should prove to be commercially productive we will then set a Bridging plug below perforations which will be made in the Rustler anhydrite below a depth of 1553 and will cement through perforations with 100 sacks. If the Grayburg does not prove to be productive we will pull as much of the 5 1/2" as is possible; set a cement plug at the top of casing left in hole; another cement plug at 2700'; and another cement plug at 1600'. We will leave the hole full of heavy mud and set the regulation marker at the surface. The location site will be cleared as per Commission requirements.

Approved....., 19.....
Except as follows:

Amco Oil & **CORDCO DRILLING CO.**
Company of Operator
By **Charles J. Miller**
Position **Agent**
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By **S. J. Stansley**
Title.....

Name **W. W. Rogers, Jr.**
Address **2807 Marquette Bank Bld'g. Dallas, Texas**