

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**SANTA FE, NEW MEXICO**

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL |  |
| NOTICE OF INTENTION TO CHANGE PLANS         |                                     | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |  |
| NOTICE OF INTENTION TO REPAIR WELL          |                                     | NOTICE OF INTENTION TO PLUG WELL                      |  |
| NOTICE OF INTENTION TO DEEPEN WELL          |                                     |   |  |

Hobbs, New Mexico

Place

October 1, 1949

Date

OIL CONSERVATION COMMISSION,  
 Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_

Stanolind Oil & Gas Company Anna L. Foster Well No. 1 in SE/4  
 Company or Operator Lease  
 of Sec. 23, T. 19, R. 33, N. M. P. M., Wildcat Field.  
Lea County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
**FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION**

On October 2, 1949, at 12:05 a.m. 48 hours will have elapsed since running 291' of 13" casing set at 303' and cemented with 300 sacks to be used as surface string. Pipe and water shut off will be tested by applying 1000 psi pressure and holding for 30 minutes before and after drilling cement plug. If pressure drop in excess of 100 psi occurs on either test proper remedial measures will be carried out. Cement will be circulated to surface. If tests are satisfactory drilling will be resumed.

OCT 4 1949

Approved \_\_\_\_\_, 19\_\_\_\_  
 except as follows:

OIL CONSERVATION COMMISSION,

By

Title

OIL & GAS INSPECTOR

Stanolind Oil and Gas Company  
 Company or Operator

By

Position Field Superintendent  
 Send communications regarding well to

Name Ralph L. Hendrickson

Address

Box F  
Hobbs, New Mexico

