

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
APR 20  
HOBB'S OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |          |  |  |
|--|----------|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |          | REPORT ON REPAIRING WELL                       |  |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |          | REPORT ON PULLING OR OTHERWISE ALTERING CASING |  |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                | <b>X</b> | REPORT ON DEEPENING WELL                       |  |
| REPORT ON RESULT OF PLUGGING OF WELL                       |          |  |  |

April 19, 1950 Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Stanolind Oil and Gas Company Anna L. Foster A Well No. 2 in the

SW/4 Company or Operator 23 Lease 19-8 in the  
of Sec. 23, T. 19-8, R. 38-E, N. M. P. M.,  
Foster-Lea Field, Lea County.

The dates of this work were as follows: April 17, 1950

Notice of intention to do the work was (~~was-not~~) submitted on Form C-102 on April 17 19 50  
and approval of the proposed plan was (~~was-not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On April 17, 1950 at 7:30 A. M., 48 hours had elapsed since cementing the oil string, 5-1/2" casing, set at 7290' and cemented with 200 sacks of cement.

Pipe and water shut-off was tested by applying 1,000 psi pressure during a period of 30 minutes before and after drilling the cement plug. No drop in pressure occurred on either test period.

Witnessed by T. S. Holden Stanolind Oil and Gas Co. Head Rsbt.

Name

Company

Title

Subscribed and sworn before me this 19th

day of April 19 50

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Ralph L. Henderson  
Position Field Superintendent

Representing Stanolind Oil and Gas Company  
Company or Operator

My commission expires 2-23-54

Address Box "F", Hobbs, New Mexico

Remarks: **APPROVED**

Date APR 20 1950

Ralph L. Henderson  
Name  
Title

THE UNIVERSITY OF CHICAGO

LIBRARY

1215 EAST 58TH STREET  
CHICAGO, ILL. 60637

ALL INFORMATION CONTAINED  
HEREIN IS UNCLASSIFIED  
DATE 10/1/80 BY SP-10/1/80

EX-100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000

100-100000-100000-100000