

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3 - OGC
1 - File

AUG 30 3 55 PM '66

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 5098-1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tidewater Oil Company	8. Farm or Lease Name State "K"
3. Address of Operator Box 249, Hobbs, New Mexico	9. Well No. 2
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 13 TOWNSHIP 20S RANGE 36E N.M.P.M.	10. Field and Pool, or Wildcat Monument
15. Elevation (Show whether DF, RT, GR, etc.) 3540 Gr.	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

It is proposed to plug and abandon this well as follows: Lay 25 sack cement plug across perforations at 3708 to 3761'. Cut off 7" casing at deepest free point and pull. Lay 25 sk cement plug across top of 7" casing. If casing is pulled from below Eumant gas zone, will isolate same with 25 sk cement plug at top of Queen at 3272, 25 sk cement plug at top of Seven Rivers at 2836' and 25 sk cement plug at top of Yates at 2550'. Will lay 25 sk cement plug across bottom of 9-5/8" casing at 2465', will cut off and pull 9-5/8" casing from lowest free point and lay 25 sk cement plug across top. If salt section exposed, will isolate same by laying 25 sack cement plugs at top and bottom. Will lay 25 sk cement plug at 13" surface casing shoe at 240'. Will lay 10 sack cement plug at surface and install dry hole marker. Mud laden fluid will be left between all plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. R. Wade TITLE Area Supt. DATE 8/29/66
APPROVED BY [Signature] TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

