

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) sand oil frac	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Monument, New Mexico  
(Place)

July 16, 1961  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

**Amerada Petroleum Corporation** State **NV** Well No. **4** in **0**  
(Company or Operator)  
**S W**  $\frac{1}{4}$  **N E**  $\frac{1}{4}$  of Sec. **36**, T. **19B**, R. **36E**, NMPM., **Monument** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to pull rods & tubing and run Gamma Ray Neutron & cement bond log. Squeeze 5-3/4" open hole from 3801 - 3908' with 75 sz reg. incor cement. Drill out to 3820' and swab test. If necessary, sand oil fracture with 10,000 gals lease oil and 5,000# 20/40 sand and 5,000# of 10/20 sand w/ Adomite added. Swab test and if unsuccessful in reducing water volume, set CI retainer @ approx. 3796' and squeeze open hole 3801-3820' with 50 sacks. Perf. 6-5/8" OD casing from 3785' to 3788' and 3790' to 3792' with 2 bullets per foot. Swab and if necessary, sand oil fracture with 6,000 gals lease oil, 3000# of 20/40 sand and 3000# of 10/20 sand w/ Adomite added. Swab and resume production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

**Amerada Petroleum Corporation**  
Company or Operator

By *[Signature]*  
Position **Asst. District Superintendent**  
Send Communications regarding well to:

Name **Amerada Petr. Corp.**

Address **Drawer D - Monument, N.M.**