Title

NEV .EXICO OIL CONSERVATION CO?

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

SION

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

indicate nature o	f notice by checking	g below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X NOTICE O	OF INTENTION TO SHOOT OR	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE O	OF INTENTION TO PULL OR	
NOTICE OF INTENTION TO REPAIR WELL		OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			
Monument, New	Place	April 12,	1937
OIL CONSERVATION COMMISSION,			
Santa Fe, New Mexico.			
Gentlemen:			
Following is a notice of intention to do certain work a	s described below a	t the	
Amerada Petroleum Corporation			NE NE
Company or Operator of Sec. 36 T 19 R 36	Lease	••	
, I, R	,N. M. P. M.,_	MOTORALE	Field
County.			
-5/8" 32# 8-Thd. New Seamless casing		ons of the commission is well at 2384° and ca	emented by
Casing and fitting will be tested with andisturbed for thirty minutes.s If no be drilled out of the casing and the samplied and allowed to stand undisturbed	was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m med.	is well at 2384° and consumer and allowed to a tre results the cement of pimp pressure will ainutes. If no drop in	stand will then
Casing and fitting will be tested with andisturbed for thirty minutes.s If no be drilled out of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resun	was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m med.	swell at 2384 and consumer and allowed to a tre results the cement	stand will then
8-5/8" 32# 8-Thd. New Seamless easing the Halliburton Method with 600 sacks. Casing and fitting will be tested with undisturbed for thirty minutes.s If no be drilled out of the casing and the sapplied and allowed to stand undisturbe results the drilling will then be resum	was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m aed.	is well at 2384' and construction and allowed to a tre results the cement of pimp pressure will ainutes. If no drop in	stand will then again be pressure
Casing and fitting will be tested with undisturbed for thirty minutes.s If no be drilled out of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund the property of the case of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund that the drilling will then be resulted as the drilling will the drilling will the drilling will then be resulted as the drilling will the drilling will be the drilli	was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m aed.	ssure and allowed to a re results the cement of pimp pressure will inutes. If no drop in	stand will then again be pressure
Casing and fitting will be tested with andisturbed for thirty minutes.s If no be drilled out of the easing and the samplied and allowed to stand undisturbe results the drilling will then be resund approved	was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m aed.	is well at 2384' and construction and allowed to a tre results the cement of pimp pressure will ainutes. If no drop in	stand will then again be pressure
Casing and fitting will be tested with undisturbed for thirty minutes.s If no be drilled out of the easing and the samplied and allowed to stand undisturbe results the drilling will then be resunded.	Was set in thi 1200# pump pre drop in pressu ame test of 120 ed for thrity m and.	ssure and allowed to a re results the cement of pimp pressure will inutes. If no drop in	stand will then again be pressure
Casing and fitting will be tested with undisturbed for thirty minutes.s If no be drilled out of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund the property of the case of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund that the drilling will then be resulted as the drilling will the drilling will the drilling will then be resulted as the drilling will the drilling will be the drilli	Was set in thi 1200# pump predrop in pressure test of 120 and for thrity made. Amerada By	ssure and allowed to a re results the cement of pimp pressure will ainutes. If no drop in Company or Operator	stand will then again be pressure
Casing and fitting will be tested with undisturbed for thirty minutes.s If no be drilled out of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund the property of the case of the casing and the samplied and allowed to stand undisturbe results the drilling will then be resund that the drilling will then be resulted as the drilling will the drilling will the drilling will then be resulted as the drilling will the drilling will be the drilli	Was set in thi 1200# pump predrop in pressure test of 120 and for thrity made. Amerada By	ssure and allowed to a re results the cement of pimp pressure will inutes. If no drop in Company or Operator Startey supit.	stand will then again be pressure

The control of the co

 $\label{eq:continuous} (1) = \frac{1}{2} \left(\frac{1$

t t ·

f(x) = f(x) + f(x) + f(x) + f(x)

1: 000 gradient state of the state of

and the second of the second o end of the second

: