

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON SQUEEZE & ACIDIZE (Other)	X

December 14, 1954

(Date)

Monument, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

State "P" Lease

DAAS Well Service
(Company or Operator)

(Lease)

McAdams Well Service

(Contractor)

Well No. 1 in the SW 1/4 SW 1/4 of Sec. 36

T. 19-S, R. 36-E, NMPM, Monument Pool, Lea County.

The Dates of this work were as follows: 7-28-54 to 9-9-54

Notice of intention to do the work (was) ~~received~~ submitted on Form C-102 on December 14, 1954.
(Cross out incorrect words.)

and approval of the proposed plan (was) ~~received~~ obtained.

3808' D.O.D.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Pulled tubing. Set magnesium retainer @ 3720'. Squeezed open hole from 3798' to 3903' w/ 150 sacks regular cement and 16 barrels of diesel oil. Drilled out to 3850'. Acidized open hole from 3798' to 3850' w/1200 gallons 15% LST acid. Tested by swabbing - No commercial production.

Set cast iron retainer @ 3786'. Squeezed open hole from 3798' to 3850' w/75 sacks regular cement. Perforated 7" OD casing from 3772' to 3782' w/ 40 bullet shots. Acidized 7" OD casing perforations from 3772' to 3782' w/2700 gallons of 15% LST acid. Tested by swabbing. No commercial production.

Set magnesium retainer @ 3734' & squeezed 7" OD casing perforation from 3772' to 3782' w/75 sacks regular cement. Drilled out to 3808' & acidized open hole from 3798' to 3808' w/ 1500 gallons 15% LST acid. Tested by swabbing & put well on pump.

9-25-54 - Pumped 52.56 bbls. oil & 21.60 bbls. water in 24 hrs.
on 13-34" SPM. Gas volume 8750 cfpd; GOR - 166

Witnessed by E.E. Shirley
(Name)

Amerada Petroleum Corporation
(Company)

Farm Boss
(Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *W. L. Smith*

Position: Foreman

Representing: Amerada Petroleum Corporation

Address: Drawer D - Monument, New Mexico

(Title)

(Date)