

MEXICO OIL CONSERVATION COMMISSION

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-869	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name State "F"
3. Address of Operator Drawer D, Monument, NM 88265		9. Well No. 1 3
4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 36 TOWNSHIP 19 S RANGE 36 E NMPM.		10. Field and Pool, or Wildcat Monument - G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3596' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

October 1977

Pulled production equipment. Checked top of fill in open hole at 3899'. Perforated Grayburg San Andres Zone in open hole from 3798' to 3802' and from 3816' to 3856' w/one 25 gm glass shot every two ft.. Checked fill in open hole at 3894'. Chemical squeezed Grayburg San Andres Zone in open hole from 3788' to 3905' w/75 bbls 2% KCL water mixed w/105 gal Protex-A11 and flushed w/25 bbls 2% KCL water mixed w/5 gal Protex-A11. CI 24 hrs and resumed pumping.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Fisher</u>	TITLE <u>Supv. Admin. Serv.</u>	DATE <u>11-4-77</u>
APPROVED BY <u>Jerry S. Smith</u>	TITLE <u>Dist. 1. Supv.</u>	DATE <u>NOV 17</u>
CONDITIONS OF APPROVAL, IF ANY:		

1942-1943

OIL CONSERVATION BOARD
HUMPHREYS, N. Y.