STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

THE PART OF THE PA		
DISTRIBUTION		
BANTA FE		
FILE	1	
U.S.O.S.	T	
LAND OFFICE		
0000000		

L CONSERVATION DIVISIO P. O. BOX 2088

Form C-103

PILE	SANTA FE, NEV	V MEXICO 87501	Kevised 19-1-7	
U.S.O.S.			5a. Indicate Type of Les	5.●
LAND OFFICE			State X Fee	
OPERATOR			5. State Oil & Gas Lease	a No.
			A-1543-1	
	NOTICES AND REPORTS ON			
1.	H FOR PERMIT -" (FORM C-101) FOR SU	CH PROPOSALS.)		7111111
OIL GAS X			7. Unit Agreement Hame	
2. Name of Operator	OTHER-		0.5	
GULF OIL CORPORATION			8. Farm or Lease Name	
3. Address of Operator			Graham State	(NCT-F)
P. O. Box 670, Hobbs,	NM 88240		5	
4. Location of Well			10. Field and Pool, or W	tideat
Р 66	O South	LINE AND 660 FEET FRO		
,,	FEET FROM THE	LINE AND UOU FEET FRO	Monument McKe	mm
THE East LINE SECTION		RANGE 36E NMP		
	TOWNSHIP	MANGE SOLL NMPI	(
	15. Elevation (Show whether		12. County	,44444;
ÖHIIIIIIIIIIIIII	3586' GI	L	Lea	
Check Ap	propriate Box To Indicate 1	Nature of Notice, Report or O	ther Data	*****
NOTICE OF INT	ENTION TO:		NT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASI	ing
TEMPORARILY ABANDON		COMMERCE DRILLING OPNS.	PLUG AND ABAN	===
PULL OR ALTER CABING	CHANGE PLANS	CASING TEST AND CEMENT JOB		<u></u> ,
-	<u>—</u>	OTHER Partial Clean	Out	
OTHE &				
17. Describe Proposed or Completed Open- work: SEE RULE 1103.	ations (Clearly state all pertinent det	1 ails, and give pertinent dates, including	ne estimated date of starting	any monored
Install BOP, pull tubing Tretolite RP2336/1000 of line, bailed fill to to Ran packer, on-off too 11,000# tension at 9744 flushed with 40 bbls 25 ISIP 600#, vacuum in 1 fill; POH with tubing, with top of liner at 95	ng & packer from hole. down casing, casing did op of CIBP at 9600'. K 1 with profile, 2-3/8" 4'. Swabbed. Pump 100 % KCL water with 1½ gal min. Attempted to swa found top of fill at 9 763'. POH with tubing. ker set at 9742-47' wit	Pumped 140 bbls 2% KCL not load. RIH with dr (nocked CIBP loose; clear tubing; landed tubing w 00 gals 15% NEFE acid wi .s RP2336. Maximum press .b; tubing has blockage. 0815'. Ran liner on tub Ran packer, profile no ch 8000# tension, profile	fresh water & 1 gill bailer on sand ned out to 9814'. ith packer set with 5 gal surfactar sure 1300# at 2 Bl Attempted to baing & set at 9815'	gal d th nt & PM, il
	,			
18. I hereby certify that the information about	Ove is true and complete to the born	f my hypothadus	· · · · · · · · · · · · · · · · · · ·	
7	A ser and complete to the pest of	my snowledge and bellef.		
ilussell (Na	Lo.		9925	(نه
BIGNED 1/ C-C-C-C-C-C-C-C-C-C-C-C-C-C-C-C-C-C-C-	TITLE	Area Engineer	_ DATE 7-23-8	
Orly, Signed by	8			
APPROVED BY FORTY SECTION			1990 56	1980
CONDITIONS OF DISPLANTED STEEL ANY:	THE		DATE	
	Expires 7	1/24/81		