

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	7"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Jul 6

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the _____
Gulf Oil Corporation Graham State "F" Well No. 5 in the _____

Company or Operator _____ of Sec. 36, T. 19 S, R. 36 E, N. M. P. M.,
SE SE Blinebry Field, Lea County.

The dates of this work were as follows: Set plugs on July 19 & 20, 1948. Tested & perforated July 21, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on July 20, 19 48
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

A 7" Lane wells Drillable Bridging Plug was set at 9735' and 25 sacks of cement was dumped on top of plug. A 2nd Lane Wells Drillable Bridging Plug was set at 6000' and 25 sacks of cement was dumped on top of plug. Top of cement was found at 5872'. After testing upper plug with 1500# pressure for 30 minutes (O.K.), 7" casing was perforated from 5710' to 5745' with six 15/32" holes per foot by Lane Wells.

Witnessed by H. L. Campbell Gulf Oil Corporation Drilling Foreman
Name Company Title
Subscribed and sworn before me this _____
22nd day of July 19 48 I hereby swear or affirm that the information given above
is true and correct.
Name E. J. Gallagher
Position District Sup't.
Representing Gulf Oil Corporation
Company or Operator
My commission expires 10-24-49 Address Box 1667, Hobbs, New Mexico

Remarks:

APPROVED

Name

Title