

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, or on plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See Special instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<input checked="" type="checkbox"/>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

August 6, 1952

Hobbs - New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Signal Oil and Gas Company

W. M. Walker

Gackle Drilling Company

Well No. 1 in the SE 1/4 SW 1/4 of Sec. 31

T. 19S, R. 38E, NMPM., Wildcat Pool, Lea County.

The Dates of this work were as follows: July 28, 1952

Notice of intention to do the work (was) ~~written~~ submitted on ~~Form C-102~~ on August 5, 1952and approval of the proposed plan (was) ~~written~~ obtained. Verbal approval by Mr. Yarborough 7/27/52

Plug #1 DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Plugged in 8-3/4" hole through 4 1/2" drill pipe @ 4160 w/140 sax of Portland regular cement. Displaced with 64 bbls. of mud. Top of plug @ 3759. Finished @ 1:00 P.M.

Plug #2 Plugged in 11" hole thru 4 1/2" drill pipe @ 2700' w/30 sax regular cement. Displaced w/37 bbls. of mud. Top of plug @ 2645. Finished 2:30PM

Plug #3 Plugged in 11" hole thru 9 1/2" drill pipe @ 1803' w/30 sax of regular cement. Displaced w/24.5 bbls. of mud. Top of plug @ 1748. Finished at 4:00 P.M.

Plug #4 Plugged in 11" hole thru 4 1/2" drill pipe @ 315' w/45 sax regular cement. Displaced w/2.3 bbls. mud. Top of plug @ 247' (13-3/8" shoe @ 275'). Finished at 6:00 P.M.

Plug #5 Plugged top of 13-3/8" surface pipe w/5 sax regular cement. Placed 4" pipe marker in top of surface extending 4" above ground.

Mud in hole - 10#/gal. 60-70 sec. viscosity

Pits have been filled and location is being levelled. Cleared of junk.

Witnessed by: Russell H. Green, Jr. Signal Oil & Gas Co. Asst. Div. Engineer

(Name)

(Company)

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Russell H. Green

Position: Asst. Division Engineer

Representing: Signal Oil and Gas Company

Address: 1010 Fort Worth Nat'l Bank Bldg.
Fort Worth 2, Texas

(Title)

(Date)

