

Now MEXICO OIL CONSERVATION COMMIS

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

JUN 3 C 34-

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission

Regulations of the Commission. Indicate nature of no	otice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PLUG OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	İ
NOTICE OF INTENTION TO DEEPEN WELL	Notice of Intention to Reduce Excessive Gas-Oil Ratio	X
Hobb	es, New Mexico June 30, 19	144
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.		
Gentlemen:		_
Following is a notice of intention to do certain work as State "K"		
of Sec. 36 T. 20S R. 36R		
County.		
RULL DEVIATES OF PR	ROPOSED PLAN OF WORK	
	S AND REGULATIONS OF THE COMMISSION	
		.m 2820
It is proposed to shut of	f the present perforations from	
It is proposed to shut of o 3840 with a bridging plug, perfo	of the present perforations from 3785	to 378
It is proposed to shut of o 3840 with a bridging plug, perfor ith nine shots and squeeze cement	of the present perforations from 3785 through these perforations und	to 378 l er a
It is proposed to shut of to 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in t	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After	to 378 ler a er ce-
It is proposed to shut of o 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable comenting tool set in the ent has set, the cement and bridging	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of 3840 with a bridging plug, perform the shots and squeeze cement etrievable comenting tool set in the ent has set, the coment and bridging put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of o 3840 with a bridging plug, perforth nine shots and squeeze cement etrievable comenting tool set in tent has set, the cement and bridgical put back on production through	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- id the
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the set, the cement and bridgitell put back on production through to 3840.	of the present perforations from 3785 through these perforations under 5-inch liner at 3775. After any plug will be drilled out any	to 378 ler a er ce- nd the
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the set, the cement and bridging put back on production through to 3840.	of the present perforations from 3785 through these perforations undine 5-inch liner at 3775. Afternation will be drilled out and the original perforations from the original perforations.	to 378 ler a er ce- id the
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the tent has set, the cement and bridging plug put back on production through the 3840.	of the present perforations from 3785 through these perforations und the 5-inch liner at 3775. After a plug will be drilled out and the original perforations from the original perforations.	to 378 ler a er ce- id the
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the set, the cement and bridging plut back on production through to 3840.	orate above the plug from 3785 through these perforations undine 5-inch liner at 3775. Afterning plug will be drilled out and the original perforations from the original perforations.	to 378 ler a er ce- id the
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the set, the cement and bridging plut back on production through the original set of the s	orate above the plug from 3785 through these perforations undine 5-inch liner at 3775. Afterning plug will be drilled out and the original perforations from the original perforations.	to 378 ler a er ce- id the om 3820
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the tent has set, the cement and bridging plut back on production through the one of 3840. Approved Approved except as follows:	orate above the plug from 3785 through these perforations under the 5-inch liner at 3775. After a plug will be drilled out and the original perforations from the original perforations from the original perforations. Shell Oil Company, Inc. Company or Operator	to 378 ler a er ce- id the om 3820
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the set, the cement and bridging plut back on production through the original set of the s	orate above the plug from 3785 through these perforations under the 5-inch liner at 3775. After any plug will be drilled out and the original perforations from the original perforations from the original perforations. Shell Oil Company, Inc.	to 378 ler a er ce- nd the om 3820
It is proposed to shut of to 3840 with a bridging plug, perfor the nine shots and squeeze cement etrievable cementing tool set in the tent has set, the cement and bridging plut back on production through the set of the s	orate above the plug from 3785 through these perforations under the 5-inch liner at 3775. After a plug will be drilled out and the original perforations from the original perforations from the original perforations from the company or Operator. By Position District Engineer.	to 378 ler a er ce- id the om 3820
It is proposed to shut of to 3840 with a bridging plug, perform the shots and squeeze cement estrievable cementing tool set in the set, the cement and bridging plut back on production through the set of the se	orate above the plug from 3785 through these perforations under the 5-inch liner at 3775. After a plug will be drilled out and the original perforations from the original perforations from the original perforations. Shell Oil Company, Inc. Company or Operator By Position District Engineer Send communications regarding well	to 378 ler a er ce- id the om 3820