

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO ABANDON Sandril	X	NOTICE OF INTENTION (OTHER) Sand Frac	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 29, 1961
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Pan American Petroleum Corporation**

W. N. Terry Tract 2 Well No. **13** in **K**
(Company or Operator) (Unit)
NE $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **10**, T. **19-S**, R. **38-E** NMPM, **Hobbs** Pool
(40-acre Subdivision)
Lea County. **3588' GL TD 4179 FBD 4083.**

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to shut off water and increase productivity of this well it is proposed to clean out to retainer set at 4080'; set drillable cement retainer at approximately 4025' and cement squeeze perforations 4040'-4078' with 100-200 sx of regular neat. Drill out to approximately 4080'; sandril perforate 4011-14, 4017-20, 4024-27, 4034-37, 4041-44, 4047-50, 4055-58, 4065-68, 4071-74, using 14 minutes jetting time at each interval. Spot 750 gallons 15% regular acid across perforations followed with a sand frac consisting of 30,000 gallons lease crude containing 2# sand per gallon. Overflush with 10 barrels of oil and restore to production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Pan American Petroleum Corporation

Original Signature of Operator
By **V. E. STALEY**

Position **Area Superintendent**
Send Communications regarding well to:

Name **V. E. Staley**
Address **Box 68, Hobbs, New Mexico**