New Mexico

orm 9-831a (Feb. 1961)	AF, TO SUBMIT IN TRIPLICATE)	Land Office.	New Mexico
	(SUBMIT IN TRIPLICATE)	Lease No	02127-B
	DEPARTMENT OF THE INGER PROPERTY OF THE INGERTY OF THE INGENERAL OF THE INGERTY OF THE INGER THE INGERTY OF THE INGERTY OF THE INGERTY OF THE INGERTY OF THE INGER THE INGER THE INGERTY OF THE IN	OR Unit	
*	L. GORDON CARLOS CHELSTER		
	SCALLE INSTRUCT ENGINEER POR		

NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA) December 3 1963
Lea Unit •W•D•Well No. 1 is located 1905 ft. from NW 1/4 SW 1/4 Sec 12 20-S	$\begin{cases} [N] \\ S \end{cases} \text{ line and } \begin{cases} 810 \\ \text{ft. from } \begin{cases} \frac{12}{W} \end{cases} \text{ line of sec.} \end{cases} $

The elevation of the derrick floor above sea level is 3665 ft.

S.W.D.

(14 Sec. and Sec. No.)

(Field)

Undesignated

DETAILS OF WORK

(County or Subdivision)

Lea

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ing points, and all other important proposed work)

Spudded 12-1/4" hole 11/18/63. Drilled to 1,360' and ran 46 jts 8-5/8" csg J-55, 24# weight, to 1357'. Cemented by Halliburton 1 plug method w/400 sax Trinity Reg w/2% gel, followed by 200 sax Trinity Reg w/2% Cacl₂. Good cement returns to surface. Plug down at 3:00 A.M. 11/23/63. W.O.C. 25 hrs. Tested csg w/1000 # for 30 min, held OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.			
Company	Marathon Oil Company		
Address	Box 220		
***************************************	Hobbs, New Mexico	By albert mechler f	
***************************************		Title Asst. Supt.	