Form 9-331 (May 1963)				THE INTERIOR (Other instructions re-			Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. LC 071900(a)			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)							6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1. OIL X GAS WELL X WELL OTHER							7. UNIT AGREEMENT NAME			
2. NAME OF OPERATOR Atlantic Richfield Company							8. FARM OR LEASE NAME Lea 6015 ARC Federal			
3. ADDRESS OF OPERATOR P. O. Box 1710, Hobbs, New Mexico 88240							9. WELL NO.			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330 FSL & 1980 FWL (Unit letter N)						10. FIELD AND POOL, OR WILDCAT Teas-Yates 7R 11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec 9, T20S, R33E				
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12.	COUNTY OR		. STATE		
		3532	3532' DF			ea	· .	N.M.		
16.	Check Ap	propriate Box To Indi	icate Natu	e of Notice, Report,	or Other	Data				
	NOTICE OF INTEN	TION TO:		s u	BSEQUENT	REPORT OF:				
TEST WATER SE FRACTURE TREA SHOOT OR ACIDI REPAIR WELL	7.10	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)		ALTE	RING CASIN	G		
(Other)	(Other) Completion or Reco						its of multiple completion on Well appletion Report and Log form.)			
Present of 9-5/8" cs 7" csg @ 5" liner Perfs 298	ondition of 2950' cmtd w 2075-3350' c 60-3004'.	RATIONS (Clearly state all mally drilled, give subsurf well: TD 3350' td w/450 sx. C/600 sx. Cmt C mtd w/90 sx. C	, PBTD 3 ant circ.	and measured and true v	dates, inchertical del control of the properties	iding estima pths for all i	ted date of markers and the control of the control	starting any d zones perti-		

Circ hole w/9.5# mud.

Set 30 sk cmt plug 1987-2163' (176')

Set 30 sk cmt plug 1225-1345' (132')

Set 10 sk cmt plug @ surface.

Note: Potash mine operators will be notified.

WI: This well is in R-III-A area. Hole must be filled with compute from 3150 to 1200 feet, and a 10-sack surface plug set. Top of cement at approximately 1200' must be verified by touching with tubing or by other means.

Approval is subject to possible future requirement that road angler pad be AMERICANT:

rection of tool rioped and relevelled

18. I hereby certify that the foregoing is true and correct		
SIGNED & Jamas	TITLE _	Dist. Drlg. Supv.
(This space for Federal or State office use)		AP AB
APPROVED BY	TITLE _	AB TO THE COURT OF THE PARTY OF
		ANTHUR 3 SNOWN STATE TO BE TO SEE

*See Instructions on Reverse Side