

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-066126

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanson D

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lynch Yates 7 River

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

S26T20R34

12. COUNTY OR PARISH

Lea

13. STATE

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Burk Royalty Co.

3. ADDRESS OF OPERATOR

P. O. Box BRC, Wichita Falls, Texas 76307

4. LOCATION OF WELL. Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

Unit Letter D, 330 ft. FNL, 330' FWL,
Sec. 26, T20, R34NMPM.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

KB 3694'; GR 3682.7'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well Completion Record:
270' 8 5/8" 14-15.5#
3728' 5 1/2"
3579' 5/8" rods

Perforating record:
8 shots from 3614' to 3618'
8 shots from 3620' to 3624'
6 shots from 3628' to 3631'

100 sxs neat cement was pumped through tubing to cover existing perfs. Perf squeezed at 3000#. 2000' or 50 bbl of salt gel (9.0 ppg.) spacer was pumped. Shot squeeze perfs at 1450 and set cement retainer at 1400 with 35' cement on top. 100' cement plug across 8 5/8" casing shoe extending 50' above/50' below casing shoe. Left 50' surface plug and erected P & A monument.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert Fowler

TITLE

Robert Fowler, Vice-President

DATE

12-17-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

6-28-88

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of well and liability under bond is required until surface restoration is completed.

*See Instructions on Reverse Side

RECEIVED
JUN 21 10 30 AM '88
GEOLOGICAL SURVEY
ALBUQUERQUE

3