NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICE

12 M 2 59 Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| NOTICE OF INTENTION | | Notice of Intention to | Notice of Intention | | |
|---|---|-------------------------------------|-------------------------------------|--|--|
| TO CHANGE PLANS | | Temporarily Abandon Well | to Drill Deeper | | |
| NOTICE OF INTENTION TO PLUG WELL | x | NOTICE OF INTENTION TO PLUG BACK | Notice of Intention to Set Liner | | |
| Notice of Intention | | NOTICE OF INTENTION | Notice of Intention | | |
| to Squeeze | | TO ACIDIZE | to Shoot (Nitro) | | |
| Notice of Intention to Gun Perforate | | Notice of Intention (Other) | Notice of Intention (Other) | | |

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs, New Mexico August 9, 1963

111

Gentlemen:

| Following is a Noti | ce of Intentio | n to do certa | un w | ork as dei | cribed | below at | the | orris R. | Antweil | |
|-----------------------|----------------|-------------------------------|-------------|------------|------------|----------|---------|----------|---------|--------|
| Julie | Ann | | | | | | | | | P |
| SE 1/4 SE | (Company or | Operator) 10 | 7T ' | 195 | | 1 36E | | | | (Unit) |
| (40-acre Subdivision) |) | ••••••••••••••••••••••••••••• | 1 | •••••• | , K | •••••• | ,NMPM., | | | Pool |

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to set a 25 sack cement plug across perforations, shoot 42" casing loose at approximately 5800'; set a 25 sack cement plug in stub of 4½"; set a 25 sx cement plug in bottom of 8-5/8" at 3300'; shoot 8-5/8" casing loose at approximately 1200'; set a 25 sx cement plug in stub of 8-5/8"; set a 25 sx cement plug in top of salt, or if less 8-5/8" is recovered, stub plug would be sufficient; set a 25 sx plug in bottom of 13" OD at 313'; set a 10 sx plug in top, with appropriate marker.

| Approved, 19, 19 | Morris R. Antweil Company or Operator By | | | | | |
|---|--|--|--|--|--|--|
| Approved OIL CONSERVATION COMMISSION | Position | | | | | |
| B# [//// | Name | | | | | |
| Title | Addama Box 2010, Hobbs, New Mexico | | | | | |