

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Manzano Oil Corporation

3. Address and Telephone No.

P.O. Box 2107, Roswell, NM 88202-2107 (505) 623-1996

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL
Sec 17, T20S, R35E

5. Lease Designation and Serial No.

NM-86172

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Appleseed Fed Com #1

9. API Well No.

30-025-20377

10. Field and Pool, or Exploratory Area

Lynch Penn.

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/24/98 Unset pkr. Pull to 10,345'. Set pkr. Acidized w/5000 gal of 20% NEFE acid. Perfs show to be communicated w/upper squeeze hole.
4/25/98 Set cement retainer @ 10,436'. Mix 125 sks of Class H .02% FL62. Squeeze perfs.
4/29/98 Reperforated 10,448-466'. TIH w/Model "R" Loc-Set pkr and set @ 10,345'.
Acidized w/3400 gal 20% NEFE.
4/30/98 Swab testing. 10th hr - 2 swab runs - FL 8000' scat to SN - Rec 15.03 BF - 50% oil, remainder emulsion.
5/01/98 Continue to swab tsq. 11th hr - 2 swab runs - FL 8000' scat to SN - Rec 11.69 BF 50% oil/emulsion.
5/02/98 Continue to swab tsq. 11th hr - 2 swab runs - FL 8800' scat to SN - Rec 10.02 BF 50% oil/50% emul.

(ORIG. SGD.) GARY GOURLEY

14. I hereby certify that the foregoing is true and correct

Signed

Alfonso Hernandez

Title

Engineering Technician

Date

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: