

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Midland, Texas

(Place)

March 18, 1964

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

JAKE L. HAMON

(Company or Operator)

H.E. Lynch Unit

Well No. 1

in E

(Unit)

SE 1/4 NE 1/4 of Sec. 17, T. 20-S, R. 35-E, NMPM, Lynch Pennsylvanian Pool

(40-acre Subdivision)

Lee

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Perforations 13,766'-13,774' and 13,714'-13,730' have already been plugged with cement in re-completion attempt. Perforations 13,659'-13,675' are shut off with Baker Model "D" packer with "DR" plug installed set at 13,628'.

Perforations 13,552'-13,566' will be plugged with 25 sack plug from 13,550'-13,452'. 7" casing will be shot off and pulled from free point somewhere above 13,288'. 25 sack cement plug will be placed in the 7" casing stub. 25 sack cement plug will be placed in the top of the Bone Spring at 8350'. 25 sack plugs will be placed in the base of the 9 5/8" casing at 5498', the stub of the 9 5/8" wherever shot off, and the base of the 13 3/8" casing at 894'. A 10 sack plug with the proper marker will be placed in the top of the 13 3/8" casing.

This program was verbally approved by Mr. Joe Ramey, New Mexico Oil Conservation Commission on March 13, 1964.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

JAKE L. HAMON

Company or Operator

By.....

H.W. Shaw

Position.....

Production Supt.

Send Communications regarding well to:

Name.....

Jake L. Hamon

Address.....

908 Vaughn Bldg., Midland, Texas