NEW MEXICO OIL CONSERVATION COMMISSIO.: Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin: A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

tional instructions in the Rules and Regulations of the Commission. Indicate Nature of Notice by Checking Below Notice of Intention Notice of Intention to NOTICE OF INTENTION TO DRILL DEEPER TEMPORARILY ABANDON WELL TO CHANGE PLANS Notice of Intention Notice of Intention X Notice of Intention TO SET LINER TO PLUG BACK TO PLUG WELL Notice of Intention NOTICE OF INTENTION Notice of Intention TO SHOOT (Nitro) TO ACIDIZE TO SQUEEZE Notice of Intention Notice of Intention Notice of Intention (OTHER) TO GUN PERFORATE OIL CONSERVATION COMMISSION March 18, 1964 Midland, Texas SANTA FE, NEW MEXICO Gentlemen: Following is a Notice of Intention to do certain work as described below at the..... No. Ro. Lynch Unit Well No. 1 in Unit JAKE L. HAMON (Company or Operator) 35-E NMPM, Lynch Permy Lyanian Pool 17 T.1/4 of Sec.... Subdivision) ____County. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Perforations 13,766 -13,774 and 13,714 -13,730 have already been plugged with sement in re-completion attempt. Perforations 13,6590-13,6750 are shut off with Baker Model "D" packer with "DR" plng installed set at 13,628". Perforations 13,5520-13,5660 will be plugged with 25 sack plug from 13,5500-13,4520. 7" casing will be shot off and pulled from free point somewhere above 13,2880. 25 sack cement plug will be placed in the 7" casing stub. 25 mack cement plug will be placed in the top of the Bone Spring at 8350°. 25 mack plugs will be placed in the base of the 9 5/8" casing at 5498°, the stub of the 9 5/8" wherever shot off, and the base of the 13 3/8" casing at 8940. A 10 sack plug with the proper marker will be placed in the top of the 13 3/80 casing. This program was verbally approved by Mr. Joe Ramey, New Mexico Oil Conservation Commission on March 13, 1964. JAKE LZ HAMON Approved... Except as follows: H.W. Shaw Position.....Production.Supt..... Send Communications regarding well to: Approved OIL CONSERVATION COMMISSION Jake L. Hamon Name..... Addres 908 Yangha Bldg Hidland, Texas