



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Hobbs, New Mexico**

Lease No. **LC-065613-B**

Unit **N.E. LYNN**

1963 JAN 23 AM 9

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 17, 1962

Well No. **1** is located **1980** ft. from **[N]** line and **660** ft. from **[E]** line of sec. **17**

**NE 17** (1/4 Sec. and Sec. No.) **20-S** (Twp.) **15-E** (Range) **New Mexico** (Meridian)  
**Wildcat** (Field) **Lea** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the ~~surface~~ **Ground** floor above sea level is **3699.7** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 170 jts of 9 5/8" OD, 36# & 41# intermediate casing & set at 5198.00' KB. Cemented with 300 lbs 50-50 Pozmix plus 6% gel and 200 lbs regular neat cement. Flng down at 1:50 a.m. 1/15/63. Found top of cement at 4000' by temperature survey. WOC 48 hrs. Tested BOP and 9 5/8" casing with 1500 psi for 30 minutes. Held O.K.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **JAKE L. RAMON**

Address **500 VAUGHN BUILDING**  
**DALLAS 1 TEXAS**

By **Frederick A. [Signature]**

Title **Chief Production Clerk**