

Jake L. Hamon, #1 Northeast Lynch Unit-Federal - Sec. 17-
Wildcat 20S-35E

2-18-63 Drlg. 11225' ls. & sd.
2-25-63 Drlg. 11737' ls. & sd.
3-4-63 Drlg. 12420' ls. & sd.
3-11-63 Drlg. 12933' ls., sh. & ch.
3-18-63 TD 13396', prep to DST.
3-25-63 TD 13416', on DST.
DST 13140-396', pkr failed.
4-1-63 Drlg. 13680' sd. & sh.
DST 13282-416', open 2 hrs 50 mins, pkr failed,
Rec 2000' HGCWB, 4150' HGCM & 3950' DM, 30"
ISIP 5733#, FP 1115-1272#.
DST 13425-500', open 2 hrs 35 mins, used 2500' WB,
Rec WB + 5590' SGC Salt Wtr, no ISIP, FP 1291-
3650#, 30" FSIP 7030#.
4-8-63 TD 13839', prep to log.
DST 13693-839', pkr failed, rec 3000' GCWB +

-cont.-

4-15-63 740' Gas Cut Mud.
TD 14157', prep to run casing.
DST 13674-839', open 49 mins, used 4000' WB,
WBIS in 37", rec 90' GC Dist. + 360' GCW & 450'
GCDist. & Wtr. + 1640' GCM, 30" ISIP 7479#, FP
2088-3007#, 2 hrs & 42 min FSIP 7468#.
TOPS BY ELECTRIC LOG: Strawn 12417', Bend 12634'.
4-22-63 Drlg. 14227' ls. & ch.
4-29-63 Drlg. 14450' ls. & ch.
5-6-63 Drlg. 14638' ls. & ch.
5-13-63 Drlg. 14839' sh.
5-20-63 TD 15040', prep to DST.
DST 14760-985', open 1'45", rec 2000' GCWB + 180'
GCM, no ISIP, FP 1105-1154#, 30" FSIP 1202#.
DST 14985-15035', open 1 hr, rec 2000' GCWB, w/tr.
oil, + 30' GCM, 30" ISIP 6325#, FP 929-988#, 30"
FSIP 6325#.
Sample Tops: B Springs Dolc. 9425', Dev. 14965'.