

APPROVED (SUBMIT IN TRIPLICATE)

SEP 16 1963 UNITED STATES

DEPARTMENT OF THE INTERIOR

J. L. GORDON GEOLOGICAL SURVEY

ACTING DISTRICT ENGINEER

Land Office

Lease No. **NM 077017**

Unit

SEP 16 1963

U. S. GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	XX		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 6, 1963

N. T. ROBERTS-FEDERAL

Well No. **1** is located **1980** ft. from **S** line and **660** ft. from **E** line of sec. **14**

SE/4 (¼ Sec. and Sec. No.)	14	20S (Twp.)	34E (Range)	N.M.P. (Meridian)
Wildcat (Field)		Lea (County or Subdivision)		New Mexico (State or Territory)

The elevation of the derrick floor above sea level is **--** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well drilled to total depth of 3715 feet with no shows of oil or gas encountered.
We propose to plug and abandon well as follows:
Mud laden fluid in hole.
100 ft. cement plug 3555 to 3655 feet
100 ft. cement plug 1750 to 1650 feet
50 ft. cement plug 860 to 810 feet
10 ft. cement plug top of surface cas.

Confirming oral approval received 9-6-63.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **J. C. MAXWELL**

Address **2017 Continental Natl. Bank**

Building


Fort Worth, Texas 76102

[Signature]

Title **Supt. of Production & Engrg.**

AP, ED

COPY TO G.C.C.



SEP 16 1963

(SUBMIT IN TRIPLICATE)

UNITED STATES

J. L. GORDON
ACTING DISTRICT ENGINEER
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. **077017**

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	XX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 1, 1963

N.T. Roberts-Federal

Well No. **1** is located **1980** ft. from **XX** line and **660** ft. from **E** line of sec. **14****SE/4****14****20S****34E****N.M.P.**

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Wildcat

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **--** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well spudded 10:30 A.M. 8-27-63. Hole size 17-1/2 inch. Ran 873.75 feet 13-3/8" 48# N-40 casing set @ 848 feet and cemented with 575 sacks cement. Plug down @ 4:10 A.M. 8-29-63. Cement circulated to surface outside casing. W.O.C. 31 hrs. Tested casing 2,000 psi - 30 minutes - O.K.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **J. C. MAXWELL**Address **2017 Continental Natl. Bank****Bldg.****Fort Worth, Texas 76102**

By

Title **Supt. of Production & Engrg.**